



**Classes:**

**\*Compact car -3 or 4 cylinder**

**\*Midsize Car- 6 cylinder**

**\*Full size car**

**\*Compact truck /SUV/ Van No V8**

**\*Compact Truck /SUV/ Van V-8 Engines**

**\* Full size Truck 2 Wheel drive**

**(4x4 must remove a drive shaft)**

## **Auto Cross Rules 2021**

- Cars and trucks must be stock appearing.
- Driver side door bars are highly recommended.
- **Must have a lap and shoulder belt, ( five point recommended) Helmet and eye protection required**
- **Must remove all glass (windshield is optional). 1 interior mirror allowed.**
- **Windshields that are removed must have 3 bars spread evenly over 3 feet**
- **Roll cage must be made of a minimum 1-3/4 inch pipe or tubing with 1/8 inch wall thickness, steel only.**

**All bars must be fully welded and should be properly fit for strong weld.**

**Hoop can't extend past cab by more than 6 inches in height and no wider than widest point of body.**

**Main hoops must also have 2 kickers from top of hoop to area closes to rear axle as possible.**

**If Vehicle if full frame cage components must be welded to frame.**

**Unibody vehicle, must use 6 inch by 6 inch plate welded to the body with cage components welded to plate**

**Driver side door bars are recommended.**

- **Bumpers may be chained or welded. Homemade replacement bumper ok, no sharp corners or any metal that is unsafe. (bumpers must remain flat, no homemade v bumpers**
- Suspension must be stock OEM (no aftermarket allowed, no relocations or modifying of any mounts
- Any DOT approved street legal tire or Hoosier, McCreary race tire allowed
- Radiator must be in stock location (electric fans allowed)

- **Battery may be moved, but must be secure (no rubber straps)**
- **Gas tanks and fuel lines may remain in stock location for the following: Cars vertically above or ahead of rear end and between frame rails in a safe location (can't be behind rear end)**
- **Tanks that are moved must be secure in box or trunk. Filler spouts should not extend past vehicle. After market tank must have check ball in line of the breathers to keep fuel from splashing out. If vehicle has an electric fuel pump and the tank is removed it must have electric shut off switch or a manual valve easily accessible**
- **Holes in firewall must be covered to prevent fire from spreading to driver**
- **Trunk tailgate and hood must be chained or welded shut as well as all doors (hood must have a 8" hole)**
- Exhaust through the hood is allowed as long as they are less than 3 feet high
- Transmission coolers are allowed
- Locked rear ends are allowed
- Split rims must be welded. Bead locks are permitted
- Numbers need to be clearly marked on both sides of vehicles or a roof sign. Roof signs must be a minimum of 18 inches by 18 inches painted black with white lettering. Minimum 1 inch wide number on roof. Numbers that are hard to read could result in laps being missed. Lap counters are not responsible for error due to this. Your vehicle number needs to be on the front grill area or where head lights are to help officials with lineups after a red flag
- Shift linkage may be removed
- Radiator protection is allowed but is to function as protection for the radiator only. Must be behind bumpers and no greater than 1-3/4 tubing same as roll bar.(not designed as battering rams or you will be asked to remove them before the race)
- Each heat will consist of 6 laps and each feature will consist of 12 laps
- No alcohol in the pits
- Must be 16 years old to participate with parents' consent form signed if under 18
- Anything not covered in the rules will be decided by the officials, officials desion is final
- Any questions please contact Jeff Nelson @ 507-202-3835

**\*Pay out\***

\$40 entry car/driver      Based on 50 cars

1st = \$250 + trophy

2<sup>nd</sup> = \$175

3<sup>rd</sup> = \$125